



Technical requirements:

- 1. Appearance requirements: no burr, cutting edge, shrinkage and other defects
- 2. This product does not contain Pb, Hg, Cd, Cr VI
- 3. Flame retardant grade: UL94V-2
- 4. This product is used at 0°C~80°C temperature
- 5. The water absorption rate of the material used in this product is 2.5% at the temperature of 23°C and 50% relative humidity for 24 hours

Application: support PC board, ensure middle not vibration, load and sag short circuit.

Item No	A	B	Packing
PDC-05	5.0	6.0	2000PCS
PDC-06	6.0	6.8	
PDC-6.5	6.5	6.8	
PDC-07	7.0	6.8	
PDC-08	8.0	6.8	
PDC-10	10.0	6.8	
PDC-15	15.0	6.8	

GENERAL TOLERANCE		PROJECTION		 Description:				
X. ±0.50		UNITS		mm		PCB Support Series		
.X ±0.25		SCALE		1:1				
.XX ±0.10		Draw by:		Jenny				
				KLS P/N:		L-KLS8-0255-PDC-05		
ANGLE TOLERANCE		Check by:		 NingBo KLS ELECTRONIC CO.,LTD.				
X. ±5°		Date					2018-03-01	
.X ±3°								
.XX ±2°		SHEET					1 OF 1	