

# Product Specification

Number: L-KLS3-MM9767P-403

Name: Mini microphone

Specification: \_\_\_\_\_

Customer: D02

Date: 2021-01-27

Customer Signature:



**NINGBO KLS ELECTRONIC CO; LTD**

Tel : 0086-574-86828566

Fax : 0086-574-86824882

ADD : NO. 8-1, RONGXIA RD. XIAPU SHANQIAN  
INDUSTRIAL ZONE BEILUN NINGBO ZHEJIANG.

Compile	Check	Review	Approval
Jenny	Jack.C		

# PRODUCT SPECIFICATION

<b>TYPE:</b> ECM	<b>PART No:</b> L-KLS3-MM9767P-403	<b>PAGE:</b> 2/8
------------------	------------------------------------	------------------

## 1、Scope

The specifications should be applied to electret condenser microphone of L-KLS3-MM9767P-403

## 2、Storage And Judgement Conditions


	Temperature Range(° C)	Rel. Humidity (%)	Static Pressure (kPa)
Judgement	19~21	60~70	86~106

## 3、Specifications

Test Conditions:  $V_s=3.0V$ ,  $R_L=2.2K\Omega$ ,  $Temp=20\pm 2^\circ C$ ,  $R.H=60\pm 5\%$

ITEM	Symbol	Test Conditions	Min	Standard	Max	Unit
Sensitivity	S	f=1KHz, S.P.L=1ubar	-43	-40	-37	dB 0dB=1V/PA
Impedance	Z	f=1KHz, S.P.L=1ubar			2.2	KΩ
Directivity	Omni-directional					
Current Consumption	I				500	μA
Operation Voltage Range	Vs		1.0	3.0	10	V
S/N Ratio	S/N(A)	f=1KHz, S.P.L=1Pa A Curve	$\geq$ 55			dB
Decreasing Voltage Characteristic	ΔS	f=1KHz, S.P.L=1Pa Vs=4.5-3.0V			-3	dB
Max. Input Sound Level	MISPL	f=1KHz, Distortion≤3%			115	dB

## 4、Frequency Response




# PRODUCT SPECIFICATION

TYPE: ECM

PART No: L-KLS3-MM9767P-403

PAGE: 3/8

## 5、 APPEARANCE & DIMENSIONS




# PRODUCT SPECIFICATION

<b>TYPE:</b> ECM	<b>PART No:</b> L-KLS3-MM9767P-403	<b>PAGE:</b> 4/8
------------------	------------------------------------	------------------


## 6、 Test Circuit

### Measurement Circuit

Vs:Source Voltage 3.0V    RL:Load Resistance 2.2K  $\Omega$



## 7、 Test Setup Drawing



# PRODUCT SPECIFICATION

**TYPE:** ECM

**PART No:** L-KLS3-MM9767P-403

**PAGE:**5/8

## 8、 Reliability Test

All tests should be done after 2 hours of conditioning at 20°C, R. H65% , while the sensitivity is to be within  $\pm 3\text{dB}$  from the initial sensitivity after the following experiments.

### 8.1 High Temperature Test

High temperature:	+80°C
Duration:	72 hours

### 8.2 Low Temperature Test

Low temperature:	-40°C
Duration:	72 hours

### 8.3 Temperature Cycle Test (See in Fig.1)

Low temperature:	-40°C
High temperature:	+80°C
Changeover time:	10min
Duration:	30min
Cycle:	32

### 8.4 Statical Humidity Test

Temperature:	+40°C
Relative humidity:	90~95%
Duration:	72hours

# PRODUCT SPECIFICATION

**TYPE:** ECM

**PART No:** L-KLS3-MM9767P-403

**PAGE:**6/8

## 8.5 Vibration Test

Amplitude :	1.52mm
Duration:	1minutes /plane
Freq.range:	10~55 Hz
Total time:	2 hours

## 8.6 Dropping Test

Drop a unit unpacked onto a board of 20mm thick.


Height:	1.0 m
Cycle:	6

## 8.7 ESD Test

The microphone under test must be discharged between each ESD exposure without ground.  
(contact:  $\pm 6KV$ , air:  $\pm 8KV$ ) There is no interference in operation after 10 times exposure.

## 9、 Regarding the Soldering operation


- Use 15~ 20W soldering iron and maintain  $290^{\circ}C \sim 310^{\circ}C$  in operation.
- Operators who work in the solder fixture and the soldering iron must be statically grounded under each soldering process.
- Soldering should be accomplished within two seconds at each terminal so as not to be overheated.
- Optimal design for heat sink pad is same as below.



# PRODUCT SPECIFICATION

<b>TYPE:</b> ECM	<b>PART No:</b> L-KLS3-MM9767P-403	<b>PAGE:</b> 7/8
------------------	------------------------------------	------------------

## 10、 List and Structure of Materials



NO	Part name	Material Type	Qty	Origin	Manufacture	Remarks
1	PCB	FR-1	1		Circuit board	
2	FET	K596	1			
3	Holder	ABS	1			
4	Back plate	Cu	1			
5	Spacer	Mylar	1			
6	Film	FEP	1			
7	Outer most shell	AL	1			
8	Cloth	Fabrics	1			

# PRODUCT SPECIFICATION

**TYPE:** ECM

**PART No:** L-KLS3-MM9767P-403

**PAGE:**8/8

## 11、 HANDLING INSTRUCTION

### 1、 Assembly process

- a)、 After connector and holder are once disassembled , they should not be re-used.
- b)、 Do not touch outer springs directly(except for PCB or proper terminal set at nominal height.
- c)、 Do not give any mechanical shocks to the micphone(e.g. dropping to floor)

### 2、 General information

2-1: This microphone shall not be operated or stored in following environment.

- >where liquid(water,solvent and so on)splashes.
- >where the air has a high concentration of corrosive gas .
- >where is too dusty.
- >where temperature changes rapidly.

2-2: Frequency response especially in high frequency region is dependent on the structure of enclosure.

Please remove additional acoustic mass or cavity in front of the microphone to the utmost.

2-3:do not put mechanical pressure more than 2 kg to the microphone.

2-4: microphone should not be in state of outgoing packing for a long-term storage.

2-5: all the soldering procedures upon microphone must be complete in a metallic device,the temperature of the soldering irons must be limited as 320℃ and less 2 s ,the operators、 the solder fixtures and the soldering irons must be statically grounded under each soldering process.