

Product Specification

Number: L-KLS3-MM6050P-403

Name: Mini microphone

Specification: _____

Customer: D02

Date: 2021-01-27

Customer Signature:



NINGBO KLS ELECTRONIC CO; LTD

Tel : 0086-574-86828566

Fax : 0086-574-86824882

**ADD : NO. 8-1, RONGXIA RD. XIAPU SHANQIAN
INDUSTRIAL ZONE BEILUN NINGBO ZHEJIANG.**

Compile	Check	Review	Approval
Jenny	Jack.C		

PRODUCT SPECIFICATION

TYPE: ECM

PART No: L-KLS3-MM6050P-403

PAGE: 2/8

1. Scope

The specifications should be applied to electret condenser microphone of L-KLS3-MM6050P-403

2. Storage And Judgement Conditions


	Temperature Range(° C)	Rel. Humidity (%)	Static Pressure (kPa)
Judgement	19~21	60~70	86~106
Storage	-30~70		
Operating	-20~60		

3. Specifications

Test Conditions: $V_S=3.0V$, $R_L=2.2K\Omega$, $Temp=20\pm2^\circ C$, $R.H=60\pm5\%$

ITEM	Symbol	Test Conditions	Min	Standard	Max	Unit
Sensitivity	S	f=1KHz, S. P. L=1Pa	-43	-40	-37	dB 0dB=1V/Pa
Impedance	Z	f=1KHz, S. P. L=1Pa			2.2	K Ω
Directivity		Omni-directional				
Current Consumption	I				500	μA
Operation Voltage Range	V_S		1.0	3.0	10	V
S/N Ratio	S/N(A)	f=1KHz, S. P. L=1Pa A Curve	55			dB
Decreasing Voltage Characteristic	ΔS	f=1KHz, S. P. L=1Pa $V_S=4.5-3.0V$			-3	dB
Max. Input Sound Level	MISPL	f=1KHz, Distortion<3%			110	dB

4. Frequency Response




PRODUCT SPECIFICATION

TYPE: ECM

PART No: L-KLS3-MM6050P-403

PAGE: 3/8

5. APPEARANCE & DIMENSIONS



PRODUCT SPECIFICATION

TYPE: ECM


PART No: L-KLS3-MM6050P-403

PAGE: 4/8


6. Test Circuit

Measurement Circuit

V_s :Source Voltage 3.0V R_L :Load Resistance 2.2K Ω



7. Test Setup Drawing



PRODUCT SPECIFICATION

TYPE: ECM

PART No: L-KLS3-MM6050P-403

PAGE:5/8

8. Reliability Test

All tests should be done after 2 hours of conditioning at 20℃, R. H65% , while the sensitivity is to be within $\pm 3\text{dB}$ from the initial sensitivity after the following experiments.

8.1 High Temperature Test

High temperature:	+80℃
Duration:	72 hours

8.2 Low Temperature Test

Low temperature:	-40℃
Duration:	72 hours

8.3 Temperature Cycle Test (See in Fig.1)

Low temperature:	-40℃
High temperature:	+80℃
Changeover time:	10min
Duration:	30min
Cycle:	32

8.4 Statical Humidity Test

Temperature:	+40℃
Relative humidity:	90~95%
Duration:	72hours

PRODUCT SPECIFICATION

TYPE: ECM

PART No: L-KLS3-MM6050P-403

PAGE:6/8

8.5 Vibration Test

Amplitude : 1.52mm
Duration: 1minutes /plane
Freq.range: 10~55 Hz
Total time: 2 hours


8.6 Dropping Test

Drop a unit unpacked onto a board of 20mm thick.

Height: 1.0 m
Cycle: 6

9. Regarding the Soldering operation


- a. Use 25~ 30W soldering iron and maintain 310°C~330°C in operation.
- b. Operators who work in the solder fixture and the soldering iron must be statically grounded under each soldering process.
- C. Soldering should be accomplished within two seconds at each terminal so as not to be overheated.
- d . Optimal design for heat sink pad is same as below.



PRODUCT SPECIFICATION

TYPE: ECM	PART No: L-KLS3-MM6050P-403	PAGE: 7/8
------------------	------------------------------------	------------------

10. List and Structure of Materials



NO.	PARTS
1	PCB
2	FET
3	Holder
4	Back plate
5	Spacer
6	Film
7	Outer most shell
8	Cloth

NO	Part name	Material Type	Qty	Origin	Manufacture	Remarks
1	PCB	FR-4	1			
2	FET	K596	1			
3	Holder	POM	1			
4	Back plate	Cu	1			
5	Spacer	Mylar	1			
6	Film	FEP	1			
7	Outer most shell	AL	1			
8	Cloth	Fabrics	1			

PRODUCT SPECIFICATION

TYPE: ECM	PART No: L-KLS3-MM6050P-403	PAGE: 8/8
------------------	------------------------------------	------------------

11. HANDLING INSTRUCTION

1、Assembly process

- a)、After connector and holder are once disassembled , they should not be re-used.
- b)、Do not touch outer springs directly(except for PCB or proper terminal set at nominal height.
- c)、Do not give any mechanical shocks to the microphone(e.g. dropping to floor)

2、General information

2-1: This microphone shall not be operated or stored in following environment.

- >where liquid(water,solvent and so on)splashes.
- >where the air has a high concentration of corrosive gas .
- >where is too dusty.
- >where temperature changes rapidly.

2-2: Frequency response especially in high frequency region is dependent on the structure of enclosure.

Please remove additional acoustic mass or cavity in front of the microphone to the utmost.

2-3:do not put mechanical pressure more than 2 kg to the microphone.

2-4: microphone should not be in state of outgoing packing for a long-term storage.

2-5: all the soldering procedures upon microphone must be complete in a metallic device,the temperature of the soldering irons must be limited as 320℃ and less 3 s ,the operators、 the solder fixtures and the soldering irons must be statically grounded under each soldering process.