









PCB LAYOUT



NOTES:

1. Rating:300V 10A;
2. Insulation Withstands Voltage:
AC2000V/MIN;
3. Insulation Resistance:
500M Ω or more at DC500V
4. Using Temperature Range:
-40°C/+105°C;
5. Screw Torque Vlaue:0.4N.m;
6. Suitable Electric Wire: 16-26AWG .
7. "★" is critical dimension to be controlled.



SECTION:A-A

Total Pitch Tolerances in mm										Nominal dimension range in mm										$\perp$		$\equiv$	$—$		$//$
over 0 to 30	over 30 to 53	over 53 to 70	over 70 to 90	over 90 to 115	over 115 to 150	over 150 to 250	over 250 to 350	over 350 to 500	over 500 to 30	over 30 to 53	over 53 to 70	over 70 to 90	over 90 to 115	over 115 to 150	over 150 to 200	over 200 to 250	over 250 to 320	over 0 to 10	over 10 to 100	all		over 0 to 100	over 100 to 150	over 150 to 300	
± 0.18	± 0.25	± 0.30	± 0.35	± 0.40	± 0.45	± 0.60	± 0.70	± 0.85	± 0.20	± 0.25	± 0.30	± 0.35	± 0.44	± 0.55	± 0.70	± 0.80	± 0.90	0.2	0.3	0.3	0.2	0.3	0.5		

ITEM	NAME OF PART		NO. OF PART		Q"TY	MATERIAL			NOTE	
DWG.	ZX	DATE			SIZE	A4	UNITS	mm	SHEET/OF	1 / 1
CHK.		DATE			SCALE	3:1				
APP.		DATE								
					NAME	KSE-500-5.00-XX				
					DWGNO.					