



\* ZBM241V marking alternatively possible

NOTES:

1. Rating: 150V 2A,
2. Insulation Withstands Voltage: AC1300V/MIN;
3. Insulation Resistance:  $\geq 500M \Omega$  or more at DC500V
4. Using Temperature Range:  $-40^{\circ}C/+105^{\circ}C$
5. Suitable Electric Wire: 20-26 AWG
6. ★ "The important dimension."

DIM	Pitch															
	2	3	4	5	6	7	8	9	10	11	12	13	14	15		
L	7.62	10.16	12.7	15.24	17.78	20.32	22.86	25.4	27.94	30.48	33.02	35.56	38.1	40.64		
A	2.54	5.08	7.62	10.16	12.7	15.24	17.78	20.32	22.86	25.4	27.94	30.48	33.02	35.56		
DIM	P	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30
		L	4.318	4.572	4.826	5.08	5.334	5.588	5.842	6.096	6.35	6.604	6.858	7.112	7.366	7.62
A	38.1	4.064	4.318	4.572	4.826	5.08	5.334	5.588	5.842	6.096	6.35	6.604	6.858	7.112	7.366	

Total Pitch	Nominal dimension range																		
	in mm																		
0	30	53	70	90	115	150	250	350	0	30	53	70	90	115	150	200	250	0	over
to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to
30	53	70	90	115	150	250	350	500	30	53	70	90	115	150	200	250	320	10	over
±0.18±0.20±0.25±0.3±0.35±0.4±0.44±0.50±0.60±0.70±0.85±0.20±0.25±0.30±0.35±0.4±0.55±0.70±0.80±0.90	0.2	0.3	0.3	0.2	0.3	0.3	0.2	0.3	0.5										

ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTE
5	END COVER		1	PA66(V0)	
4	SPRING COIL		P	STAINLESS	
3	SOLDER PIN		P	BRASS	Tin Plated
2	LEVER		P	POM(V2)	
1	HOUSING		P	PA66(V0)	

  

DWG	CXL	DATE	NO. OF PART	SIZE	A4	UNITS	mm	SHEET/OF	1/1
			14,09,27						

  

CHK	DATE	SCALE	NAME
		2:5:1	KSE-141V-2.54-XXP

  

APP.	DATE	DWGNO.

