

CABTITE BP 21MM PA**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Similar to illustration**

Similar to illustration

The blanking plugs are used for the safe closing of
unneeded cable passages in the sealing elements.

General ordering data

Version	Blind plug, Cabtite (cable entry system), Polyamide, red, Height: 30 mm, Width: 21 mm, Depth: 30 mm, -60 °C... 100 °C, IP66
Order No.	2652450000
Type	CABTITE BP 21MM PA
GTIN (EAN)	4050118662559
Qty.	50 pc(s).

CABTITE BP 21MM PA**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data**Dimensions and weights**

Depth	30 mm	Depth (inches)	1.181 inch
Height	30 mm	Height (inches)	1.181 inch
Width	21 mm	Width (inches)	0.827 inch
Length	30 mm	Length (inches)	1.181 inch
Diameter	21 mm	Net weight	2.1 g

Temperatures

Operating temperature	-60 °C... 100 °C	Operating temperature, min.	-60 °C
Operating temperature, max.	100 °C		

General information

Halogen	No	Material	Polyamide
Outer cable diameter, max.	21 mm	Outer cable diameter, min.	21 mm
Protection degree	IP66	UL 94 flammability rating	V-0

Classifications

ETIM 6.0	EC000879	ETIM 7.0	EC000879
ETIM 8.0	EC000879	ECLASS 9.0	27-14-44-21
ECLASS 9.1	27-14-44-21	ECLASS 10.0	27-14-44-21
ECLASS 11.0	27-14-44-21	ECLASS 12.0	27-14-08-07

Approvals

ROHS	Conform
------	---------

Downloads

Engineering Data	CAD data – STEP
User Documentation	Cabtite Installation Instructions
Catalogues	Catalogues in PDF-format