


SOT-23

BAT54 MARKING: KL1

SOT-23 贴片塑封肖特基二极管**SOT-23 Plastic-Encapsulate Schottky Barrier Diode****特征 Features**

- 大电流承受能力。High Current Capability
- 正向压降低。Low Forward Voltage Drop
- 开关速度快。Extremely Fast Switching Speed

机械数据 Mechanical Data






- 封装: SOT-23 封装 SOT-23 Small Outline Plastic Package
- 环氧树脂 UL 易燃等级 Epoxy UL: 94V-0
- 安装位置: 任意 Mounting Position: Any

极限值和温度特性(TA = 25°C 除非另有规定)**Maximum Ratings & Thermal Characteristics** (Ratings at 25°C ambient temperature unless otherwise specified.)

参数 Parameters	符号 Symbol	界限 Limit	单位 Unit
最大可重复峰值反向电压 Maximum repetitive peak reverse voltage	V _{RRM}	30	V
最大均方根电压 Maximum RMS voltage	V _{RMS}	21	V
最大直流阻断电压 Maximum DC blocking voltage	V _{DC}	30	V
最大正向平均整流电流 Maximum average forward rectified current	I _{FM}	200	mA
峰值正向浪涌电流 8.3ms 单一正弦半波 Peak forward surge current 8.3 ms single half sine-wave	I _{FSM}	600	mA
典型热阻 Typical thermal resistance	R _{θJA}	500	°C/W
功率消耗 Power Dissipation	P _D	300	mW
结温 Junction Temperature	T _j	125	°C
存储温度 Storage temperature range	T _{STG}	-50~+150	°C

电特性 (TA = 25°C 除非另有规定)**Electrical Characteristics** (Ratings at 25°C ambient temperature unless otherwise specified.)


参数 Parameters	符号 Symbol	测试条件 Test conditions	Min	Typ	Max	单位 Unit
最大正向电压 Maximum forward voltage	V _{F1}	I _F = 0.1mA			240	mV
	V _{F2}	I _F = 1.0mA			320	
	V _{F3}	I _F = 10mA			400	
	V _{F4}	I _F = 30mA			500	
	V _{F5}	I _F = 100mA			1000	
最大反向电压 Maximum reverse breakdown voltage	V _R	I _R =100uA	30			V
最大反向电流 Maximum reverse current	I _R	V _R =25V			2.0	uA
典型结电容 Type junction capacitance	C _j	V _R = 1.0V, f = 1MHz			10	pF
反向恢复时间 Reverse Recovery time	t _{rr}	I _F =I _R =10mA I _{rr} =0.1X I _R , R _L =100 Ω			5	ns

Typical Characteristics**SOT-23 PACKAGE OUTLINE** Plastic surface mounted package

SYMBOL	DIMENSIONS	
	MIN	MAX
A	0.900	1.150
A1	0.000	0.100
A2	0.900	1.050
b	0.300	0.500
c	0.080	0.150
D	2.800	3.000
E	1.200	1.400
E1	2.250	2.550
e	0.950TYP	
e1	1.800	2.000
L	0.550REF	
L1	0.300	0.500
θ	0°	8°

Unit: mm

焊盘设计参考 Precautions: PCB Design(Recommended land dimensions for SOT-23 diode. Electrode patterns for PCBs)



Note:
 1. Controlling dimension: In millimeters.
 2. General tolerance: ± 0.05 mm.
 3. The pad layout is for reference purposes only.