

Model :	YSP40
Power:	36W max.
Input :	100-240VAC 50/60Hz
Output Voltage:	9-55V
Output Current:	0.1-4A
Input current:	0.8A max.
Inrush Current:	50 Amps max. at 230VAC/50Hz,full load
Leakage Current:	0.25mA Max. at 264VAC input
Power Consumption:	36W max.
Data Rate:	10/100/1000Mbps
LED Indicator:	AC power, POE active
Output Connectors:	RJ45(data+power)
Interface	1 "data" in RJ45 Ethernet port 1 "data+power" output RJ45 Ethernet port 1 AC input power socket for external
Protections :	Short Circuit /Over Current /Over Voltage
Short Circuit Protection (SCP) :	Protection to Zero Voltage
Over Voltage Protection (OVP):	$\leq V_{out} \times 150\%$
Over Current Protection (OCP):	110%-180%
Operating Ambient Temperature.:	-20°C-45°C
Operating Humidity :	Maximum 90%, Non-condensing
Storage Temperature	-20 ~ +70°C
Storage Humidity	Maximum 90%, Non-condensing
Compliance	IEEE802.3at/af (POE), CE, RoHS, Reach
Applications:	IP Phones,Wireless Networks Access Points, IP print servers, Blue tooth access points, IP Cameras, UPS, Switch, Smart door system and more.
MTBF:	100,000 hours minimum at full load at 25 ambient
Warranty	3- 5years alternative
Dimension:	120*60*36mm
Weight:	260g
Packing:	20PCS/CTN,40*30*20cm