

AST120-20XXOF



RoHS

3-Year Warranty

- Universal 85 - 264VAC or 120 - 370VDC input voltage
- High power density, compact size: 3" × 2" × 1.22"
- Operating ambient temperature range:
-40°C to +85°C
- Active PFC
- High I/O isolation test voltage up to 4000VAC
- Operating altitude up to 5000m
- Extremely low leakage current < 0.1mA
- Stand-by power consumption 0.5W Typ.
- The base plate with conformal coating
- Output short circuit, over-current, over-voltage,
Over-temperature protection
- Efficiency up to 95%
- Suitable for BF application
- 5 years warranty
- Installing in system of Safety Class I/II is available

Description

AST120-20XXOF series is suitable for all kinds of BF type (be accessible to patients) medical system equipment. It features universal AC input and at the same time accepts DC input voltage, cost-effective, high efficiency, high reliability and double or reinforced insulation.

Selection Guide

Certification	Part No.*	Nominal Output Power (W)	Nominal Output Voltage and Current (Vo/Io)	Transient Output Power*10S (W)	Output Voltage Adjustable Range (V)	Efficiency at 230VAC (%) Typ.	Max. Capacitive Load (μF)
/	AST120-2012OF	114	12V/9.5A	141.6	11.4-12.6	94	6000
	AST120-2015OF	114	15V/7.6A	142.5	14.3-15.8	94	5000
	AST120-2019OF	119.7	19V/6.3A	149	17.3-19.8	93	4500
	AST120-2024OF	120	24V/5A	150	22.8-25.2	95	3200
	AST120-2027OF	119.9	27V/4.44A	149.8	25.6-28.4	95	2400
	AST120-2036OF	120	36V/3.33A	149.76	35.28-37.8	94	2000
	AST120-2048OF	120	48V/2.5A	150	45.6-50.4	94.5	1600
	AST120-2054OF	120	54V/2.22A	149.58	51.3-55.5	94	1300

Note: 1.*If the total output power exceeds the nominal output power, it can be maintained for a maximum of 10s. The power supply cannot exceed the transient power. When the output voltage is increased, the total output power cannot exceed the nominal output power;
2.*The maximum transient output power interval must be greater than 30 minutes;

Input Specifications

Item	Operating Conditions		Min.	Typ.	Max.	Unit
Input Voltage Range	AC input		85	--	264	VAC
	DC input		120	--	370	VDC
Input Voltage Frequency			47	--	63	Hz
Input Current	115VAC		--	--	2	A
	230VAC		--	--	1	
Inrush Current	115VAC	Cold start	--	40	--	
	230VAC		--	75	--	
Power Factor	115VAC	Full load	0.98	--	--	--
	230VAC		0.94	--	--	

Input Specifications

Item	Operating Conditions	Min.	Typ.	Max.	Unit
Leakage Current	240VAC	<0.1mA; Single fault<0.5mA			
Hot Plug		Unavailable			

Output Specifications

Item	Operating Conditions		Min.	Typ.	Max.	Unit
Output Voltage Accuracy*	Full load range	12V/15V	--	±2.0	--	%
		19V/24V/27V/36V/48V/54V	--	±1.0	--	
Line Regulation	Rated load		--	±0.5	--	
Load Regulation	0% - 100% load		--	±1.0	--	
Ripple & Noise*	20MHz bandwidth (peak-to-peak value)	12V/15V	--	--	120	mV
		19V/24V/27V	--	--	150	
		36V/48V/54V	--	--	200	
Temperature Coefficient			--	±0.03	--	%/℃
Minimum Load			0	--	--	%
Hold-up Time	230VAC, 25℃		15	--	--	ms
Stand-by Power Consumption			--	0.5	--	W
Short Circuit Protection	Recovery time < 3s after the short circuit disappear		Hiccup, continuous, self-recover			
Over-current Protection			≥130% Io, hiccup, self-recover			
Over-voltage Protection	12V		≤16V (Output voltage turn off, re-power on for recover)			
	15V		≤25V (Output voltage turn off, re-power on for recover)			
	19V		≤25V (Output voltage turn off, re-power on for recover)			
	24V		≤32V (Output voltage turn off, re-power on for recover)			

Output Specifications

Item	Operating Conditions	Min.	Typ.	Max.	Unit
Over-voltage Protection	27V	≤35V (Output voltage turn off, re-power on for recover)			
	36V	≤50V (Output voltage turn off, re-power on for recover)			
	48V	≤60V (Output voltage turn off, re-power on for recover)			
	54V	≤60V (Output voltage turn off, re-power on for recover)			
Over-temperature Protection		Output voltage turn off, re-power on to recover after abnormal removed			

Note: 1. *Output voltage accuracy: including the setting error, line regulation, load regulation;
2. *The “Tip and barrel method”is used for ripple and noise test, output parallel 10uF electrolytic capacitor and 0.1uF ceramic capacitor, please refer to AC-DC Converter Application Notes for specific information;
3. *For all the above test items, please refer to our company standard "AC-DC Black Box Test Specification" for specific test specifications and methods;
*When the product works at light load (≤15% IO), in order to improve the efficiency to reach at green working mode, the value of ripple and noise will be double.

General Specifications

Item		Operating Conditions	Min.	Typ.	Max.	Unit
Isolation Test	Input -	Electric strength test for 1min., leakage current <10mA	1500	--	--	VAC
	Input - output		4000	--	--	
	Output -		1500	--	--	
Insulation Resistance	Input -	Ambient temperature: 25 ± 5°C Relative humidity: < 70%RH, no condensation Test voltage: 500VDC	100	--	--	MΩ
	Input - output		100	--	--	
	Output -		100	--	--	
Isolation level	Input - output		2 × MOPP			
	Input -		1 × MOPP			
	Output -		1 × MOPP			
Operating Temperature			-40	--	+85	°C
Storage Temperature			-40	--	+85	
Storage Humidity		Non-condensing	10	--	95	% RH
Operating Humidity			20	--	90	

General Specifications

Item	Operating Conditions		Min.	Typ.	Max.	Unit
Power Derating	Operating temperature derating	+50°C to +85°C Air cooling	2.0	--	--	% / °C
		+55°C to +85°C 10CFM				
		-40°C to -30°C	2.0	--	--	
	Input voltage derating	85VAC-115VAC Air cooling	1.0	--	--	% / VAC
		85VAC-100VAC 10CFM	2.0	--	--	
Safety Standard	12V/15V/24V/27V/48V		IEC/UL62368-1, ES60601-1, IS13252 (Part1) safety approved & EN62368-1, EN60335-1, EN61558-1, EN60601-1, BS EN62368-1 (Report) Design refer to IEC/EN/UL62368-1, EN60335-1, IEC/EN61558-1, GB4943.1, IEC/EN60601-1, ES60601-1(3.1 version), CAN/CSA-C22.2 No.60601-1:14-Edition 3, EN60601-1-2 Edition 4 IEC60950-1			
	36V		ES60601, IS13252 (Part1) safety approved & EN60601-1, BS EN62368-1 (Report) Design refer to IEC/EN/UL62368-1, EN60335-1, IEC/EN61558-1, GB4943.1, IEC/EN60601-1, ES60601-1(3.1 version), CAN/CSA-C22.2 No.60601-1:14-Edition 3, EN60601-1-2 Edition 4 IEC60950-1			
	19V		IS13252 (Part1) safety approved & EN62368-1, BS EN62368-1 (Report) Design refer to IEC/EN/UL62368-1, EN60335-1, IEC/EN61558-1, GB4943.1, IEC/EN60601-1, ES60601-1(3.1 version), CAN/CSA-C22.2 No.60601-1:14-Edition 3, EN60601-1-2 Edition 4 IEC60950-1			
	54V		EN62368-1, BS EN62368-1 (Report) Design refer to IEC/EN/UL62368-1, EN60335-1, IEC/EN61558-1, GB4943.1, IEC/EN60601-1, ES60601-1(3.1 version), CAN/CSA-C22.2 No.60601-1:14-Edition 3, EN60601-1-2 Edition 4			
Safety Class			CLASS I (with PE and must be connected)/ CLASS II (without PE)			
MTBF	MIL-HDBK-217F @ 25°C		> 300,000 h			
Warranty	Ambient temperature: <50°C		5 years			

Mechanical Specifications

Case Material	Open frame
Dimensions	76.20mm x 50.80mm x 31.00mm
Weight	125g (Typ.)
Cooling Method*	Air cooling / 10CFM


Note: *Cooling method and power derating refer to typical characteristic curves.

EMC Specifications

Emissions	CE	CISPR32/EN55032 CLASS B
	RE	CISPR32/EN55032 (Category I, CLASS B, category II, CLASS A)
	Harmonic current	IEC/EN61000-3-2 CLASS A and CLASS D
	Voltage flicker	IEC/EN61000-3-3
Immunity	ESD	IEC/EN 61000-4-2 Contact $\pm 8\text{KV}$ /Air $\pm 15\text{KV}$ perf. Criteria A
	RS	IEC/EN 61000-4-3 10V/m perf. Criteria A
	EFT	IEC/EN 61000-4-4 $\pm 2\text{KV}$ perf. Criteria A
	Surge	IEC/EN 61000-4-5 line to line $\pm 2\text{KV}$ /line to ground $\pm 4\text{KV}$ perf. Criteria A
	CS	IEC/EN61000-4-6 10 Vr.m.s perf. Criteria A
	Voltage dips, short interruptions and voltage variations immunity	IEC/EN61000-4-11 0%, 70% perf. Criteria B



Note: 1.*The power supply should be considered as a part of the components in the system. All EMC performance are been tested on a metal plate with a thickness of 1mm and a length of 360mm × 360mm. The power supply must be combined with the terminal equipment for electromagnetic compatibility confirmation;
2.*Category I products with PE (which must be connected), category II products without PE.

Product Characteristic Curves




Note: With an AC input voltage between 85 - 115VAC and a DC input between 120 - 160VDC the output power must be derated as per the temperature derating curves.

Product Characteristic Curves





Dimensions and Recommended Layout

Open-frame
units: mm [inch]
general tolerance: ±1.00 [±0.039]



CONNECTORS		
Function	Product Connector	Customer Connector
AC connector	JST B3P-VH or equivalent	Housing: JST VHR Contact: JST SVH-21T-P1.1 or equivalent
DC connector	JST B4P-VH or equivalent	Housing: JST VHR Contact: JST SVH-21T-P1.1 or equivalent



MOUNTING SCREWS			
Position	Screw Spec.	L (recommended)	Torque
①~④	M3	6mm	0.4 N·m

PIN-OUT	
PIN	Function
1	AC (N)
2	NC
3	AC (L)
4, 5	-Vo
6, 7	+Vo

Note: 1. Class I system ①, ④ positions must be connected to the protective earth ground (⊕).
2. Class II system ①, ④ positions must be connected together.
3. It is recommended that a minimum distance of 10mm be placed between the PCB edge and all other components.

- Note:
- Unless otherwise specified, parameters in this datasheet were measured under the conditions of Ta=25°C, humidity<75%RH with nominal input voltage and rated output load;
 - All index testing methods in this datasheet are based on our company corporate standards;
 - In order to improve the efficiency at high input voltage, there will be audible noise generated, but it does not affect product performance and reliability;
 - We can provide product customization service, please contact our technicians directly for specific information;
 - Products are related to laws and regulations: see "Features" and "EMC";
 - Our products shall be classified according to ISO14001 and related environmental laws and regulations, and shall be handled by qualified units;
 - CAUTION: Double pole, neutral fusing. Disconnect mains before servicing."/"ATTENTION: Double pôle/fusible sur le neutre. Débrancher l'alimentation avant l'entretien;
 - The power supply is considered a component which will be installed into a terminal equipment. All EMC tests should be confirmed with the final equipment. Please consult our FAE for EMC test operation instructions;