



MATERIAL&FINISH

Insulator: PBT Glass Fiber(UL94V-0)
 Contact :phosphor bronze
 Contact : Gold-Plated Over Nickel.
SPECIFICATIONS
 Current Rating :1A AC,DC
 Voltage Rating : 250V AC,DC
 Temperature Range:-40° C To+105° C
 Contact Resistance:20mΩ Min
 Insulation Resistance:1000MΩ Min
 Withstanding Voltage:500V AC/Min

PIN OF NO	Dim. A	Dim. B	Dim. C
06P	11.30	5.30	4.30
08P	13.30	7.30	6.30
10P	15.30	9.30	8.30
12P	17.30	11.30	10.30
14P	19.30	13.30	12.30
16P	21.30	15.30	14.30
18P	23.30	17.30	16.30
20P	25.30	19.30	18.30
22P	27.30	21.30	20.30
24P	29.30	23.30	22.30
26P	31.30	25.30	24.30
28P	33.30	27.30	26.30
30P	35.30	29.30	28.30
32P	37.30	31.30	30.30
34P	39.30	33.30	32.30
36P	41.30	35.30	34.30
40P	45.30	39.30	38.30
44P	49.30	43.30	42.30
46P	51.30	45.30	44.30
50P	55.30	49.30	48.30
60P	65.30	59.30	58.30
64P	69.30	63.30	64.30

Total Pitch Tolerances in mm										Nominal dimension range in mm										⊥	≡	—	//
over 0 to 30	over 30 to 53	over 53 to 70	over 70 to 90	over 90 to 115	over 115 to 150	over 150 to 250	over 250 to 350	over 350 to 500	over 500 to 1000	over 0 to 30	over 30 to 53	over 53 to 70	over 70 to 90	over 90 to 115	over 115 to 150	over 150 to 200	over 200 to 250	over 250 to 320	over 320 to 10	over 10 to 100	over 100 to 150	over 150 to 150	
±0.18	? .20	±0.25	±0.3	±0.35	? .44	±0.60	±0.70	? .85	±0.20	±0.25	±0.30	±0.35	±0.44	±0.55	±0.70	±0.80	±0.90	0.2	0.3	0.3	0.2	0.3	0.5

ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTE
DWG.	DATE		SIZE	A4 UNITS mm	SHEET/OF 1/1
CHK.	DATE		SCALE		
APP.	DATE		NAME	IDC2-XXF	
			DWGNO.		